

## C401 4:1 PRODUCTION CLEAR LV



PART# C401-G | 1 Gallon | CASE QTY 4

Toucan Refinishes 4:1 Clear LV C401 is a high performance 4:1 2.1 VOC production clear. Using the latest European technology, C401 delivers superb performance for an outstanding value.

# HARDENERS SLOW NORMAL FAST H416/H417/H418 4:1



PART# H416-Q PART# H417-Q PART# H418-Q CASE QTY 6

#### C400 4:1 PRODUCTION CLEAR



PART# C400-G | 1 Gallon | CASE QTY 4

Toucan Refinishes 4:1 Clear C400 is a high performance 4:1 production clear. Using the latest European technology, C400 delivers superb performance for an outstanding value.

#### HARDENERS SLOW NORMAL FAST H406/H407/H408 4:1



1 Quart PART# H406-Q PART# H407-Q PART# H408-Q CASE QTY 6

#### C201 2:1 HS EURO CLEAR LV



PART# C201-5 | 5 Litre | CASE QTY 4

Toucan Refinishes 2:1 HS Euro Clear LV C201 is a high solid European 2.1 VOC clear that provides a high gloss and long lasting finish. It has a simple 2:1 mixing ratio and does not require reducer, making it extremely economical to use.

#### HARDENERS SLOW NORMAL FAST H316/H317/H318 2:1



**2.5 Litre**PART# H316-2.5
PART# H317-2.5
PART# H318-2.5
CASE QTY 4

#### C200 2:1 HS EURO CLEAR



**PART# C200-5** | 5 Litre | CASE QTY 4 **PART# C200-1** | 1 Litre | CASE QTY 6

Toucan Refinishes 2:1 HS Euro Clear C200 is a high solid European clear that provides a high gloss and long lasting finish. It has a simple 2:1 mixing ratio and does not require reducer, making it extremely economical to use.

#### HARDENERS SLOW NORMAL FAST H306/H307/H308 2:1







**2.5 Litre**PART# H306-2.5
PART# H307-2.5
PART# H308-2.5
CASE QTY 4

1 Litre PART# H306-1 PART# H307-1 PART# H308-1 CASE QTY 6 **500 ML** PART# H307-0.5 CASE QTY 6

## P401 DTM PRIMER-SEALER LV



PART# P401-3.5 | 3.5 Litre | CASE QTY 2

Toucan Refinishes DTM Primer - Sealer LV P401 is a very versatile Low VOC primer that allows painters to use it as a primer-filler, a primer-sealer, or a full wet-on-wet sealer. This is achieved by simply increasing or decreasing the reducer depending on what they want to achieve. Mixing ratio is 4:1 using 2:1 hardener.

### HARDENER

H317 / H318 2:1



1 Litre PART# H318-1 CASE QTY 6

**2.5 Litre**PART# H317-2.5
CASE QTY 4

#### P400 DTM PRIMER-SEALER



PART# P400-3.5 | 3.5 Litre | CASE QTY 2 PART# P400-1 | 1 Litre | CASE QTY 6

Toucan Refinishes DTM Primer - Sealer P400 is a very versatile primer that allows painters to use it as a primer-filler, a primer-sealer, or a full wet-on-wet sealer. This is achieved by simply increasing or decreasing the reducer depending on what they want to achieve. Mixing ratio is 4:1 using 2:1 hardener.

### HARDENERS

H307/H308 2:1



1 Litre PART# H307-1 PART# H308-1 CASE QTY 6



**500 ML**PART# H307-0.5
CASE QTY 6

## BCJB JET BLACK LV [FACTORY PACK]



PART# BC-JB-3.5 | 3.5 Litre | CASE QTY 2

Toucan Refinishes Jet Black LV BC-JB provides excellent coverage and jet black color with a simple 2:1 mixing ratio, along with a very attractive price.

#### BIOO SUPERFIL BODY-FILLER



PART# B100-3 | 3 Litre | CASE QTY 4 PART# B100-0.75 | 0.75 Litre | CASE QTY 6

Toucan Refinishes Superfil Body-Filler B100 is made from the highest quality raw materials. This light weight filler is tack free and has a creamy texture so it's easy to spread and sand, making it perfect for steel surfaces of any size.

## AUTOMOTIVE MASKING TAPES

#### 922 ORANGE MASKING TAPE



**PART# 922-18x50 |** 3/4" (18mm) x50M CASE QTY 48

**PART# 922-36x50 I** 1.5" (36mm) x50M CASE QTY 24

High Performance automotive tape, good adhesion & resistance to lifting, clean removal with no adhesive transfer when exposed to 100°C for 30 minutes, solvent & water resistant, good flexibility on curved surfaces.



#### 80 Cases/Pallet

Tensile Strength, N/ 100mm - 385 Adhesion to Steel, N/ 100mm - 28

#### 933 YELLOW MASKING TAPE



**PART# 933-18x50 |** 3/4" (18mm) x50M CASE QTY 48

PART# 933-36x50 | 1.5" (36mm) x50M CASE QTY 24

Premium Performance Automotive Tape. Excellent Adhesion & resistance to lifting & curling, Clean removal with no adhesive transfer when exposed to 110°C for 60 min, UV, Solvent & Water Resistant, Superb flexibility on curved surfaces.



#### 80 Cases/Pallet

Tensile Strength, N/ 100mm - 485 Adhesion to Steel, N/ 100mm - 29

## TOUCANREFINISHES.COM

Logicar Inc. 1361 NW 155th Drive, Miami, FL 33169-5723, USA Email us: sales@toucanrefinishes.com | Call us: 1-888-815-2278